



ILLUMINOTECHNICAL

Luminous efficiency 100% (DLOR 4%, ULOR 96%).
 Initial luminous flux of the luminaire 6498 lm.
 Asymmetric direct-indirect distribution.
 Average luminance <math><1000\text{ cd/m}^2</math> for radial angles >math>65^\circ</math>.
 Beam angle: 108° - 110°.
 Luminous efficacy 116 lm/W.
 Lifetime (L93/B10): 30000 h. (tq+25°C)
 Lifetime (L90/B10): 50000 h. (tq+25°C)
 Lifetime (L85/B10): 80000 h. (tq+25°C)
 Lifetime (L80/B10): 100000 h. (tq+25°C)
 Sudden decreased luminous flux after 50000 hours: 0% (C0).
 Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471).
 In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards.

SOURCE

4 linear LED modules 12W/840.
 Energy efficiency class (UE 2019/2020 - UE 2019/2015): D.
 CIE 13.3 Colour rendering index: CRI >80 (R9 <math><50\%</math>).
 IES TM-30 Fidelity Index: Rf = 84 Rg = 95.
 CCT nominal colour temperature 4000 K.
 Colour initial tolerance (MacAdam): SDCM 3.

MECHANICAL

Housing in galvanized steel, painted in white epoxy-polyester with reticular slots for high direct light emission.
 Opal polycarbonate shielding film over the lower reticular zone.
 Asymmetric flow recuperator, high efficiency, in specular aluminium with superficial titanium-magnesium treatment.
 Opal acrylic upper diffuser.
 Luminaire with limited surface temperature. - D - (EN 60598-2-24)
 Dimensions: 675x230 mm, height 80 mm. Weight 2.675 kg.
 IP40 protection degree.
 Glow-wire test resistance 850°C.

ELECTRICAL

Halogen Free electronic wiring 230V-50/60Hz, power factor 0.95, THD <math><25\%</math>, constant output current, SELV, class I, 1 driver.
 Power of the luminaire 56 W.
 CE - IEC 60598-1 - EN 60598-1.
 SAFE FLICKER: PstLM=<math><1</math> and SVM=<math><0.4</math> (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light.
 Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.
 Ambient temperature from 0°C to +25°C.
 Temperature class T6 max 85°C.
 Relative humidity UR: <math><85\%</math>.

INSTALLATION

Wall.
 All accessories dedicated to this product are available on the Catalog and on our website www.3F-Filippi.com.

APPLICATIONS

Environments where a comfortable light is required. Luminaire for wall mounting, with an essential and modern design. Suitable for offices, conference rooms, managerial offices.

WARNING

Luminaire designed for disposal/recycling at end-of-life.
 Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Performances are measured and certified by our CTFs2 Photometric Laboratory (EN 13032, IES LM79); Test and Inspections (EN IEC 60598-1, CISPR 15, IEC 61547). Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

Dimensions and specifications subject to alterations without notice.

ST.20251219 - Page 1 of 1

3F Filippi S.p.A.

Via del Savena 28, Z.I. Piastrella - 40065 Pian di Macina, Pianoro (Bologna), Italy
 Tax Code. 01033260371 - VAT no. IT00529461204 - Share Capital € 3,000,000 fully paid up
 Bologna Register of Companies no. 01033260371 - REA (economic administrative index) No. 234613

Web www.3F-Filippi.com
e-Mail 3F-Filippi@3F-Filippi.it
Telephone +39.051.6529611
Fax +39.051.775884