



L	600 mm
A	600 mm
H	40 mm

ILLUMINOTECHNICAL

Luminous efficiency 100% (DLOR 100%, ULOR 0%).
Initial luminous flux of the luminaire 4029 lm.
Emergency luminaire luminous flux BLF 19.8%.
Direct symmetric distribution.
Installation Interdistance Transv.D = 1.39 x hu - Long.D = 1.39 x hu.
Average luminance <1500 cd/m² for radial angles >65°.
Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 17.2 - 17.1.
Beam angle: 93° - 92°.
Luminous efficacy 139 lm/W.
Lifetime (L95/B10): 30000 h. (tq+25°C)
Lifetime (L90/B10): 50000 h. (tq+25°C)
Lifetime (L80/B10): 80000 h. (tq+25°C)
Lifetime (L75/B10): 100000 h. (tq+25°C)
Sudden decreased luminous flux after 50000 hours: 0% (C0).
Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471).
In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards.

SOURCE

Squared LED module 25W/830.
Energy efficiency class (UE 2019/2020 - UE 2019/2015): C.
CIE 13.3 Colour rendering index: CRI >80 (R9 <50%).
IES TM-30 Fidelity Index: Rf = 84 Rg = 95.
CCT nominal colour temperature 3000 K.
Colour initial tolerance (MacAdam): SDCM 3.

MECHANICAL

Housing in hot-galvanised steel, painted in white polyester.
Honeycombed diagonal screen in white anti-glare polycarbonate.
Rhomboidal lenses with differentiated surfaces, etched and prismatic to optimise the orientation of the luminous flux, in transparent methacrylate (PMMA).
Luminaire with limited surface temperature. - D - (EN 60598-2-24)
Dimensions: 600x600 mm, height 40 mm. Weight 7.02 kg.
IP43 protection degree for exposed part, IP20 for recessed part.
Mechanical strength to impacts IK06 (1 joule).
Glow-wire test resistance 650°C.

ELECTRICAL

Halogen Free electronic wiring 230V-50/60Hz, power factor 0.90, THD <25%, constant output current, class I, 1 driver.
Power of the luminaire 29 W.
CE - IEC 60598-1 - EN 60598-1.
EP maintained emergency wiring on board, 1h duration, 24h recharge; compliant with EN 60598-2-22, excluding high risk areas.
SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light.
Ambient temperature from +5°C to +25°C.
Temperature class T6 max 85°C.
Quick connection.
Relative humidity UR: <85%.

INSTALLATION

Ceiling.
Height only 40 mm.
All accessories dedicated to this product are available on the Catalog and on our website www.3F-Filippi.com.

ACCESSORIES

A0686 - 596x596 Diagon frame for Ceiling installation.

APPLICATIONS

Environments: staterooms, with VDTs, offices.
Environments with exacting visual tasks, where diffused soft light for optimum visual comfort is required.

WARNING

Luminaire designed for disposal/recycling at end-of-life.
Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Performances are measured and certified by our CTFs2 Photometric Laboratory (EN 13032, IES LM79); Test and Inspections (EN IEC 60598-1, CISPR 15, IEC 61547). Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).