



ILLUMINOTECHNICAL

Luminous efficiency 100% (DLOR 90%, ULOR 10%).
 Initial luminous flux of the luminaire 2335 lm.
 Emergency luminaire luminous flux BLF 15.7%.
 Diffused symmetric distribution.
 Installation Interdistance Transv.D = 1.26 x hu - Long.D = 1.25 x hu.
 Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 20.4 - 20.4.
 Beam angle: 117° - 116°.
 Luminous efficacy 117 lm/W.
 Lifetime (L93/B10): 30000 h. (tq+25°C)
 Lifetime (L90/B10): 50000 h. (tq+25°C)
 Lifetime (L85/B10): 80000 h. (tq+25°C)
 Lifetime (L80/B10): 100000 h. (tq+25°C)
 Sudden decreased luminous flux after 50000 hours: 0% (C0).
 Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471).
 In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards.

SOURCE

Circular LED module 22W/940.
 Energy efficiency class (UE 2019/2020 - UE 2019/2015): E.
 CIE 13.3 Colour rendering index: CRI >90 (R9 >50%).
 IES TM-30 Fidelity Index: Rf = 92 Rg = 101.
 CCT nominal colour temperature 4000 K.
 Colour initial tolerance (MacAdam): SDCM 3.

MECHANICAL

Housing in glazed self-extinguishing V2 polycarbonate, UV stabilised, injection moulded.
 Ecologic anti-aging injected sealing gasket.
 Gear-tray reflector unit in aluminium, painted in white epoxy-polyester, fixed to the housing by quick-fastening steel devices, hinged opening.
 Diffuser in opal methacrylate (PMMA), injection moulded.
 Snug fit safety snap-lock clips for diffuser mounting in transparent polycarbonate, screwdriver opening.
 Luminaire with limited surface temperature. - D - (EN 60598-2-24)
 Dimensions: diameter 380 mm, height 117 mm. Weight 2 kg.
 IP64 protection degree.
 Mechanical strength to impacts IK02 (0.2 joule).
 Glow-wire test resistance 650°C.

ELECTRICAL

Halogen Free electronic wiring 230V-50/60Hz, power factor 0.90, THD <25%, constant output current, SELV, class I, 1 driver.
 Power of the luminaire 20 W.
 CE - IEC 60598-1 - EN 60598-1.
 EP maintained emergency wiring on board, 1h duration, 24h recharge; compliant with EN 60598-2-22, excluding high risk areas.
 SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light.
 Ambient temperature from +5°C to +25°C.
 Temperature class T6 max 85°C.
 Relative humidity UR: <85%.

INSTALLATION

Ceiling / Wall.

APPLICATIONS

Suitable product for food production plants (HACCP), IFS (Food), BRC (GSFS Food).
 Transit areas, stairwells. Environments where a diffused lighting provides visual comfort.
 Virtually in all environments compatibly with the emissions/atmospheres compromising the use of plastic materials. Not suitable for installation on surfaces subject to important vibrations, exposed to weather conditions.

WARNING

Luminaire designed for disposal/recycling at end-of-life.
 Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Performances are measured and certified by our CTFs2 Photometric Laboratory (EN 13032, IES LM79); Test and Inspections (EN IEC 60598-1, CISPR 15, IEC 61547). Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

Dimensions and specifications subject to alterations without notice.

ST.20260410 - Page 1 of 1

3F Filippi S.p.A.

Via del Savena 28, Z.I. Piastrella - 40065 Pian di Macina, Pianoro (Bologna), Italy
 Tax Code. 01033260371 - VAT no. IT00529461204 - Share Capital € 3,000,000 fully paid up
 Bologna Register of Companies no. 01033260371 - REA (economic administrative index) No. 234613

Web www.3F-Filippi.com
e-Mail 3F-Filippi@3F-Filippi.it
Telephone +39.051.6529611
Fax +39.051.775884