



L	300 mm
A	160 mm
H	100 mm

### ILLUMINOTECHNICAL

Luminous efficiency 100% (DLOR 98%, ULOR 2%).  
 Emergency luminaire luminous flux 557 lm.  
 Controlled symmetric distribution.  
 Installation Interdistance Transv.D = 0.56 x hu - Long.D = 1.18 x hu.  
 Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 20.2 - 19.3.  
 Beam angle: 36° - 98°.  
 Lifetime (L93/B10): 30000 h. (tq+25°C)  
 Lifetime (L90/B10): 50000 h. (tq+25°C)  
 Sudden decreased luminous flux after 50000 hours: 0% (C0).  
 Photobiological safety in compliance with IEC/TR 62778: RGO risk exempt, (IEC 62471).  
 In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards.

### SOURCE

Linear LED module 6W/840.  
 Energy efficiency class (UE 2019/2020 - UE 2019/2015): D.  
 CIE 13.3 Colour rendering index: CRI >80 (R9 <50%).  
 IES TM-30 Fidelity Index: Rf = 84 Rg = 95.  
 CCT nominal colour temperature 4000 K.  
 Colour initial tolerance (MacAdam): SDCM 3.

### MECHANICAL

Self-extinguishing V2 polycarbonate housing, injection moulded, RAL 7035 grey.  
 Ecologic anti-aging injected sealing gasket.  
 Gear-holder reflector in hot-dip galvanised steel, painted with white polyester base.  
 Diffuser in self-extinguishing V2 polycarbonate, photo-engraved interior, UV stabilised, injection moulded with smooth outer surface.  
 Snug fit safety snap-lock clips for diffuser mounting in stainless steel, screwdriver opening.  
 Luminaire with limited surface temperature. - D - (EN 60598-2-24)  
 Dimensions: 300x160 mm, height 100 mm. Weight 0.92 kg.  
 IP66 protection degree.  
 Mechanical strength to impacts IK10 (20 joule).  
 Glow-wire test resistance 850°C.

### ELECTRICAL

Power of the luminaire 1 W.  
 CE - IEC 60598-1 - EN 60598-1.  
 ENP non-permanent emergency wiring, 1h duration, 24h recharge;  
 compliant with EN 60598-2-22, excluding high risk areas.  
 Ambient temperature from +5°C to +25°C.  
 Temperature class T6 max 85°C.  
 Relative humidity UR: <85%.

### INSTALLATION

Ceiling / Wall.  
 All accessories dedicated to this product are available on the Catalog and on our website [www.3F-Filippi.com](http://www.3F-Filippi.com).

### APPLICATIONS

Suitable product for food production plants (HACCP), IFS (Food), BRC (GSFS Food).  
 Dry, dusty indoor environments, subject to occasional water splashes.  
 Virtually shatterproof polycarbonate compatibly with the fumes / atmospheres that compromise the elasticity of plastic materials.  
 Not suitable for installation on surfaces subject to important vibrations, exposed to weather conditions, on ropes or poles.  
 Suitable for illumination of public car parks and parking grounds referred to DIN 67528:2018-04.

### WARNING

Fixture not suitable for cold stores with an ambient temperature <5°C and/or relative humidity >85%.  
 Luminaire designed for disposal/recycling at end-of-life.  
 Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Performances are measured and certified by our CTFs2 Photometric Laboratory (EN 13032, IES LM79); Test and Inspections (EN IEC 60598-1, CISPR 15, IEC 61547). Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

Dimensions and specifications subject to alterations without notice.

ST.20260211 - Page 1 of 1

### 3F Filippi S.p.A.

Via del Savena 28, Z.I. Piastrella - 40065 Pian di Macina, Pianoro (Bologna), Italy  
 Tax Code. 01033260371 - VAT no. IT00529461204 - Share Capital € 3,000,000 fully paid up  
 Bologna Register of Companies no. 01033260371 - REA (economic administrative index) No. 234613

**Web** [www.3F-Filippi.com](http://www.3F-Filippi.com)  
**e-Mail** [3F-Filippi@3F-Filippi.it](mailto:3F-Filippi@3F-Filippi.it)  
**Telephone** +39.051.6529611  
**Fax** +39.051.775884