



L	1265 mm
A	235 mm
H	135 mm

## ILLUMINOTECHNICAL

Luminous efficiency 100% (DLOR 96%, ULOR 4%).  
 Initial luminous flux of the luminaire 15494 lm.  
 Symmetric distribution.  
 Installation Interdistance Transv.D = 1.09 x hu - Long.D = 1.25 x hu.  
 Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 24.6 - 25.2.  
 Beam angle: 87° - 106°.  
 Luminous efficacy 167 lm/W.  
 Lifetime (L97/B10): 30000 h. (tq+25°C)  
 Lifetime (L95/B10): 50000 h. (tq+25°C)  
 Lifetime (L92/B10): 80000 h. (tq+25°C)  
 Lifetime (L90/B10): 100000 h. (tq+25°C)  
 Lifetime (L90/B10): 50000 h. (tq+35°C)  
 Sudden decreased luminous flux after 50000 hours: 0% (C0).  
 Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471).  
 In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards.

## SOURCE

Linear LED module 90W/840.  
 Source with special protection against aggressive chemically-volatile substances for standard LED technology.  
 Energy efficiency class (UE 2019/2020 - UE 2019/2015): C.  
 CIE 13.3 Colour rendering index: CRI >80 (R9 <50%).  
 IES TM-30 Fidelity Index: Rf = 84 Rg = 95.  
 CCT nominal colour temperature 4000 K.  
 Colour initial tolerance (MacAdam): SDCM 3.

## MECHANICAL

Single-piece housing in pressed steel, powder-coated in white epoxy-polyester.  
 Polycarbonate screen etched internally, V2 self-extinguishing, UV stabilised, injection moulded.  
 Ecologic anti-aging injected sealing gasket.  
 Oversized gear-tray reflector unit in highly reflective white painted hot-galvanised steel.  
 Galvanised steel snap-lock clips for diffuser mounting (safety n° 4 per fixture).  
 Luminaire with limited surface temperature. - D - (EN 60598-2-24)  
 Dimensions: 1265x235 mm, height 135 mm. Weight 7.575 kg.  
 IP65 protection degree.  
 Mechanical strength to impacts IK09 (10 joule).  
 Glow-wire test resistance 850°C.

## ELECTRICAL

Halogen Free DALI-2 DATI (Parts 251, 252, 253), PUSH-DIM, electronic wiring 230V-50/60Hz, power factor 0.97 at full load, THD <25%, constant output current, class I, 1 driver, 1 DALI address.  
 Power of the luminaire 93 W.  
 ENEC - CE.  
 SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light.  
 Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 15% in DC.  
 Ambient temperature from -20°C to +35°C.  
 Temperature class T6 max 85°C.  
 Quick connection via M20 3P connector with 9-13 mm tightening range.  
 Relative humidity UR: <85%.

## INSTALLATION

Ceiling / Suspended / Wall.  
 All accessories dedicated to this product are available on the Catalog and on our website [www.3F-Filippi.com](http://www.3F-Filippi.com).

## APPLICATIONS

Suitable product for food production plants (HACCP), IFS (Food), BRC (GSFS Food).  
 Dry, dusty indoor environments, subject to occasional water splashes.  
 Industrial environments, warehouses, environments where security locks are required on all clips, e.g. prisons (on request).  
 Environments in which it is necessary a total protection against falling fragments (eg environments with foodstuffs or machines with moving parts or with extreme temperature changes), use luminaires with laminated glass.

## LIGHT MANAGEMENT

Recommended minimum setting: 10%.  
 The luminaire, equipped with (DALI-2 DATI) driver, can be controlled manually with 3F Easy Dim technology or automatically/manually with wired or wireless DALI/D2D control systems.  
 The D2D driver guarantees interoperability with other devices with the same certification by making the following information available:  
 Device Data (Part 251), Energy Report (Part 252), Diagnosis & Maintenance (Part 253).  
 In electrical systems without a regulation system (manual or automatic) and DALI bus, a suitable jumper must be made on the DA-DA terminals of the appliance.

## WARNING

Fixture not suitable for cold stores with an ambient temperature <0°C and/or relative humidity >85%.  
 Luminaire designed for disposal/recycling at end-of-life.  
 Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Performances are measured and certified by our CTFs2 Photometric Laboratory (EN 13032, IES LM79); Test and Inspections (EN IEC 60598-1, CISPR 15, IEC 61547). Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).