



L	1265 mm
A	235 mm
H	105 mm

## ILLUMINOTECHNICAL

Luminous efficiency 100% (DLOR 100%, ULOR 0%).  
 Initial luminous flux of the luminaire 6966 lm.  
 Emergency luminaire luminous flux BLF 7.1%.  
 Wide symmetric distribution.  
 Installation Interdistance Transv.D = 1.31 x hu - Long.D = 1.31 x hu.  
 Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 19.8 - 21.  
 Beam angle: 90° - 99°.  
 Luminous efficacy 124 lm/W.  
 Lifetime (L93/B10): 30000 h. (tq+25°C)  
 Lifetime (L90/B10): 50000 h. (tq+25°C)  
 Lifetime (L85/B10): 80000 h. (tq+25°C)  
 Lifetime (L80/B10): 100000 h. (tq+25°C)  
 Sudden decreased luminous flux after 50000 hours: 0% (C0).  
 Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471).  
 In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards.

## SOURCE

2 linear LED modules 24W/840.  
 Energy efficiency class (UE 2019/2020 - UE 2019/2015): D.  
 CIE 13.3 Colour rendering index: CRI >80 (R9 <50%).  
 IES TM-30 Fidelity Index: Rf = 84 Rg = 95.  
 CCT nominal colour temperature 4000 K.  
 Colour initial tolerance (MacAdam): SDCM 3.

## MECHANICAL

Single-piece housing in pressed steel, powder-coated in white epoxy-polyester.  
 Moulded anti-glare glass, non-combustible, tempered, mounted and locked to the single-piece galvanised steel perimetrical frame, sealing gasket, hinged opening by means of galvanised steel clips.  
 Wide flow recuperator, oversized, in specular aluminium with superficial titanium-magnesium treatment, non-iridescent.  
 Gear-tray unit in hot-galvanised steel, painted in white polyester, fixed to the housing by means of "Ribloc" rapid devices in galvanised steel, hinged opening.  
 Luminaire with limited surface temperature. - D - (EN 60598-2-24)  
 Dimensions: 1265x235 mm, height 105 mm. Weight 8.515 kg.  
 IP65 protection degree.  
 Mechanical strength to impacts IK09 (10 joule).  
 Glow-wire test resistance 960°C.

## ELECTRICAL

Halogen Free electronic wiring 230V-50/60Hz, power factor 0.95, THD <25%, constant output current, SELV, class I, 1 driver.  
 Power of the luminaire 56 W.  
 CE - IEC 60598-1 - EN 60598-1.  
 EP maintained emergency wiring on board, 1h duration, 24h recharge; compliant with EN 60598-2-22, excluding high risk areas.  
 SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light.  
 Ambient temperature from +5°C to +25°C.  
 Temperature class T6 max 85°C.  
 Relative humidity UR: <85%.

## INSTALLATION

Ceiling / Suspended / Wall.  
 All accessories dedicated to this product are available on the Catalog and on our website [www.3F-Filippi.com](http://www.3F-Filippi.com).

## APPLICATIONS

In industrial environments, stores and dry, dusty indoor environments, subject to occasional water splashes.

## WARNING

Fixture not suitable for cold stores with an ambient temperature <5°C and/or relative humidity >85%.  
 Luminaire designed for disposal/recycling at end-of-life.  
 Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Performances are measured and certified by our CTFs2 Photometric Laboratory (EN 13032, IES LM79); Test and Inspections (EN IEC 60598-1, CISPR 15, IEC 61547). Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

Dimensions and specifications subject to alterations without notice.

ST.20251220 - Page 1 of 1

## 3F Filippi S.p.A.

Via del Savena 28, Z.I. Piastrella - 40065 Pian di Macina, Pianoro (Bologna), Italy  
 Tax Code. 01033260371 - VAT no. IT00529461204 - Share Capital € 3,000,000 fully paid up  
 Bologna Register of Companies no. 01033260371 - REA (economic administrative index) No. 234613

**Web** [www.3F-Filippi.com](http://www.3F-Filippi.com)  
**e-Mail** [3F-Filippi@3F-Filippi.it](mailto:3F-Filippi@3F-Filippi.it)  
**Telephone** +39.051.6529611  
**Fax** +39.051.775884