



L	757 mm
A	542 mm
H	133 mm

Industrial luminaire with high light output and high luminous efficiency designed with the most innovative technologies for environments with temperature up to 55°C.

ILLUMINOTECHNICAL

Luminous efficiency 100% (DLOR 98%, ULOR 2%).
 Initial luminous flux of the luminaire 29375 lm.
 Direct symmetric wide distribution: the illuminated area has a rectangular shape.
 Installation Interdistance Transv.D = 1.24 x hu - Long.D = 1.20 x hu.
 Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 23.2 - 23.2.
 Beam angle: 82° - 83°.
 Luminous efficacy 135 lm/W.
 Lifetime (L97/B10): 30000 h. (tq+25°C)
 Lifetime (L95/B10): 50000 h. (tq+25°C)
 Lifetime (L92/B10): 80000 h. (tq+25°C)
 Lifetime (L90/B10): 100000 h. (tq+25°C)
 Lifetime (L90/B10): 50000 h. (tq+55°C)
 Sudden decreased luminous flux after 50000 hours: 0% (C0).
 Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471).
 In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards.

SOURCE

4 Mid-Power linear LED modules 50W/840.
 Source with special protection against aggressive chemically-volatile substances for standard LED technology.
 Energy efficiency class (UE 2019/2020 - UE 2019/2015): C.
 CIE 13.3 Colour rendering index: CRI >80 (R9 <50%).
 IES TM-30 Fidelity Index: Rf = 84 Rg = 95.
 CCT nominal colour temperature 4000 K.
 Colour initial tolerance (MacAdam): SDCM 3.

MECHANICAL

Passive modular heatsinks in die-casted aluminium, painted in white colour.
 To optimize the thermal management of the LED module, the heatsinks are oversized and provided with self-cleaning of cooling fins.
 Wiring body in aluminium and galvanised steel anchored solidly to the sinks and thermally separated.
 3F Lens lenses with high luminous efficiency, transparent methacrylate (PMMA), fixed to the LED modules.
 Fixing brackets in stainless steel.
 Luminaire with limited surface temperature. - D - (EN 60598-2-24)
 Dimensions: 757x542 mm, height 133 mm. Weight 19.385 kg.
 IP65 protection degree.
 Mechanical strength to impacts IK06 (1 joule).
 Glow-wire test resistance 650°C.

ELECTRICAL

Halogen Free DALI-2 DAT1 (Parts 251, 252, 253), PUSH-DIM, electronic wiring 230V-50/60Hz, power factor 0.97 at full load, THD <25%, constant output current, class I, 1 driver, 1 DALI address.
 Power of the luminaire 218 W.
 ENEC - CE.
 Flicker: <4%.
 Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 15% in DC.
 Ambient temperature from -30°C to +55°C.
 Temperature class T6 max 85°C.
 Quick connection via M25 5P connector with 9-13 mm tightening range.
 Power unit positioned on a separate compartment by the LED module to ensure optimum temperatures of cabling components, to be inspectable and maintainable.
 Relative humidity UR: <85%.

INSTALLATION

Ceiling / Suspended / Wall.
 All accessories dedicated to this product are available on the Catalog and on our website www.3F-Filippi.com.

ACCESSORIES

A0812 - Anti-glare micropismatic VS moulded glass, tempered, not flammable, with sealing gasket.
 One required for each light module. The pack contains 10 pieces.

APPLICATIONS

In commercial environments, exhibition and industrial areas, stores, open areas.
 Applications with high ambient temperature up to 55°C.
 Environments in which it is necessary a total protection against falling fragments (eg environments with foodstuffs or machines with moving parts or with extreme temperature changes), use luminaires with polycarbonate lenses.

LIGHT MANAGEMENT

Recommended minimum setting: 10%.
 The luminaire, equipped with (DALI-2 DAT1) driver, can be controlled manually with 3F Easy Dim technology or automatically/manually with wired or wireless DALI/D2D control systems.
 The D2D driver guarantees interoperability with other devices with the same certification by making the following information available:
 Device Data (Part 251), Energy Report (Part 252), Diagnosis & Maintenance (Part 253).
 In electrical systems without a regulation system (manual or automatic) and DALI bus, a suitable jumper must be made on the DA-DA terminals of the appliance.

WARNING

Fixture not suitable for cold stores with an ambient temperature <0°C and/or relative humidity >85%.
 Luminaire designed for disposal/recycling at end-of-life.
 Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Performances are measured and certified by our CTFs2 Photometric Laboratory (EN 13032, IES LM79); Test and Inspections (EN IEC 60598-1, CISPR 15, IEC 61547). Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

Dimensions and specifications subject to alterations without notice.

ST.20260410 - Page 1 of 1

3F Filippi S.p.A.

Via del Savena 28, Z.I. Piastrella - 40065 Pian di Macina, Pianoro (Bologna), Italy
 Tax Code. 01033260371 - VAT no. IT00529461204 - Share Capital € 3,000,000 fully paid up
 Bologna Register of Companies no. 01033260371 - REA (economic administrative index) No. 234613

Web www.3F-Filippi.com
e-Mail 3F-Filippi@3F-Filippi.it
Telephone +39.051.6529611
Fax +39.051.775884