



L	1270 mm
A	100 mm
H	100 mm

ILLUMINOTECHNICAL

Luminous efficiency 100% (DLOR 89%, ULOR 11%).
 Initial luminous flux of the luminaire 3619 lm.
 Direct symmetric distribution.
 Installation Interdistance Transv.D = 1.39 x hu - Long.D = 1.21 x hu.
 Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 23.8 - 20.7.
 Beam angle: 149° - 108°.
 Luminous efficacy 129 lm/W.
 Lifetime (L96/B10): 30000 h. (tq+25°C)
 Lifetime (L93/B10): 50000 h. (tq+25°C)
 Lifetime (L89/B10): 80000 h. (tq+25°C)
 Lifetime (L85/B10): 100000 h. (tq+25°C)
 Lifetime (L90/B10): 50000 h. (tq+35°C)
 Sudden decreased luminous flux after 50000 hours: 0% (C0).
 Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471).
 In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards.

SOURCE

Linear LED module 24W/840.
 Energy efficiency class (UE 2019/2020 - UE 2019/2015): D.
 CIE 13.3 Colour rendering index: CRI >80 (R9 <50%).
 IES TM-30 Fidelity Index: Rf = 84 Rg = 95.
 CCT nominal colour temperature 4000 K.
 Colour initial tolerance (MacAdam): SDCM 3.

MECHANICAL

Self-extinguishing V2 polycarbonate housing, injection moulded, RAL 7035 grey.
 Ecologic anti-aging injected sealing gasket.
 Soft opal diffuser in self-extinguishing V2 polycarbonate, photo-engraved interior, UV stabilised, injection moulded.
 Gear-holder reflector in hot-dip galvanised steel, painted with white polyester base.
 Snug fit safety snap-lock clips for diffuser mounting in stainless steel, screwdriver opening.
 Fixing brackets in stainless steel.
 Possibility for technicians to access the interior of the luminaire.
 Luminaire with limited surface temperature. - D - (EN 60598-2-24)
 Dimensions: 1270x100 mm, height 100 mm. Weight 2.03 kg.
 IP66 protection degree.
 Mechanical strength to impacts IK10 (20 joule).
 Glow-wire test resistance 850°C.

ELECTRICAL

Halogen Free DALI-2 DATI (Parts 251, 252, 253), PUSH-DIM, electronic wiring
 230V-50/60Hz, power factor 0.90 at full load, THD <25%, constant output current, SELV, class I, 1 driver, 1 DALI address.
 Power of the luminaire 28 W.
 ENEC - CE.
 SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light.
 Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 15% in DC.
 Ambient temperature from -20°C to +35°C.
 Temperature class T6 max 85°C.
 Relative humidity UR: <85%.

INSTALLATION

Ceiling / Suspended / Wall.
 All accessories dedicated to this product are available on the Catalog and on our website www.3F-Filippi.com.

APPLICATIONS

Suitable product for food production plants (HACCP), IFS (Food), BRC (GSFS Food).
 Dry, dusty indoor environments, subject to occasional water splashes.
 Luminaires designed for diffuse direct/indirect lighting suitable to provide optimum visual comfort.
 Transit areas, stairwells.
 Virtually shatterproof polycarbonate compatible with the fumes / atmospheres that compromise the elasticity of plastic materials.
 Suitable for illumination of public car parks and parking grounds referred to DIN 67528:2018-04.

LIGHT MANAGEMENT

Recommended minimum setting: 10%.
 The luminaire, equipped with (DALI-2 DATI) driver, can be controlled manually with 3F Easy Dim technology or automatically/manually with wired or wireless DALI/D2D control systems.
 The D2D driver guarantees interoperability with other devices with the same certification by making the following information available:
 Device Data (Part 251), Energy Report (Part 252), Diagnosis & Maintenance (Part 253).
 In electrical systems without a regulation system (manual or automatic) and DALI bus, a suitable jumper must be made on the DA-DA terminals of the appliance.

WARNING

Fixture not suitable for cold stores with an ambient temperature <0°C and/or relative humidity >85%.
 Luminaire designed for disposal/recycling at end-of-life.
 Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Performances are measured and certified by our CTFs2 Photometric Laboratory (EN 13032, IES LM79); Test and Inspections (EN IEC 60598-1, CISPR 15, IEC 61547). Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

Dimensions and specifications subject to alterations without notice.

ST.20260311 - Page 1 of 1

3F Filippi S.p.A.

Via del Savena 28, Z.I. Piastrella - 40065 Pian di Macina, Pianoro (Bologna), Italy
 Tax Code. 01033260371 - VAT no. IT00529461204 - Share Capital € 3,000,000 fully paid up
 Bologna Register of Companies no. 01033260371 - REA (economic administrative index) No. 234613

Web www.3F-Filippi.com
e-Mail 3F-Filippi@3F-Filippi.it
Telephone +39.051.6529611
Fax +39.051.775884