



L	1200 mm
A	300 mm
H	81 mm

## ILLUMINOTECHNICAL

Luminous efficiency 100% (DLOR 100%, ULOR 0%).  
 Initial luminous flux of the luminaire 7032 lm.  
 Direct symmetric distribution.  
 Installation Interdistance Transv.D = 1.17 x hu - Long.D = 1.18 x hu.  
 Average luminance <3000 cd/m<sup>2</sup> for radial angles >65°.  
 Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 19.6 - 19.6.  
 Beam angle: 87° - 87°.  
 Luminous efficacy 117 lm/W.  
 Lifetime (L93/B10): 30000 h. (tq+25°C)  
 Lifetime (L90/B10): 50000 h. (tq+25°C)  
 Lifetime (L85/B10): 80000 h. (tq+25°C)  
 Lifetime (L80/B10): 100000 h. (tq+25°C)  
 Sudden decreased luminous flux after 50000 hours: 0% (C0).  
 Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471).  
 In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards.

## SOURCE

Linear LED module 43W/830 + compact LED module 10W/830.  
 Energy efficiency class (UE 2019/2020 - UE 2019/2015): C, D.  
 CIE 13.3 Colour rendering index: CRI >80 (R9 <50%).  
 IES TM-30 Fidelity Index: Rf = 84 Rg = 95.  
 CCT nominal colour temperature 3000 K.  
 Colour initial tolerance (MacAdam): SDCM 3.

## MECHANICAL

Extruded aluminium housing with linear side grooves.  
 Steel end caps.  
 Black colour body and heads RAL 9011 matt with embossed finish for maximum resistance to touch and scratches.  
 Removable flow recuperator.  
 LGS micro-prismatic flat diffuser in transparent methacrylate (PMMA), multi-lenticular exterior, anti-glare.  
 Anti-glare opal polycarbonate filter for brightness uniformity.  
 Invisible interior spot in lateral position for accent or service lighting.  
 Internal parabolic element in black aluminium.  
 Luminaire with limited surface temperature. - D - (EN 60598-2-24)  
 Dimensions: 1200x300 mm, height 81 mm. Weight 8.82 kg.  
 IP40 protection degree.  
 Mechanical strength to impacts IK02 (0.2 joule).  
 Glow-wire test resistance 650°C.

## ELECTRICAL

Halogen Free DALI-2, PUSH-DIM, electronic wiring 230V-50/60Hz, power factor 0.95 at full load, THD <25%, constant output current, SELV, class I, 2 driver, 2 DALI addresses.  
 Power of the luminaire 60 W.  
 CE - IEC 60598-1 - EN 60598-1.  
 SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light.  
 Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 15% (Direct) - 100% (Spot) in DC.  
 Ambient temperature from 0°C to +25°C.  
 Temperature class T6 max 85°C.  
 5-pole terminal block, single 230V circuit.  
 5-pole transparent power cable protrudes by 1.5 m with sheared end.  
 Relative humidity UR: <85%.

## INSTALLATION

Ceiling / Suspended.  
 All accessories dedicated to this product are available on the Catalog and on our website [www.3F-Filippi.com](http://www.3F-Filippi.com).

## APPLICATIONS

Environments: with VDTs, meeting rooms, offices.  
 Environments: architectural, commercial, staterooms, banks.  
 Environments where dynamic, soft and diffuse light is required for optimal visual comfort.

## LIGHT MANAGEMENT

Recommended minimum setting: 10%.  
 The device, equipped with DALI-2 driver, can be controlled manually with 3F Easy Dim technology or automatically/manually with 3F Smart Dimming technology and/or centralised DALI systems.  
 DALI-2 certification guarantees interoperability with other devices with the same certification.  
 In electrical systems without a regulation system (manual or automatic) and DALI bus, a suitable jumper must be made on the DA-DA terminals of the appliance.

## WARNING

Luminaire designed for disposal/recycling at end-of-life.  
 Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Performances are measured and certified by our CTFs2 Photometric Laboratory (EN 13032, IES LM79); Test and Inspections (EN IEC 60598-1, CISPR 15, IEC 61547). Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

Dimensions and specifications subject to alterations without notice.

ST.20260311 - Page 1 of 1

## 3F Filippi S.p.A.

Via del Savena 28, Z.I. Piastrella - 40065 Pian di Macina, Pianoro (Bologna), Italy  
 Tax Code. 01033260371 - VAT no. IT00529461204 - Share Capital € 3,000,000 fully paid up  
 Bologna Register of Companies no. 01033260371 - REA (economic administrative index) No. 234613

**Web** [www.3F-Filippi.com](http://www.3F-Filippi.com)  
**e-Mail** [3F-Filippi@3F-Filippi.it](mailto:3F-Filippi@3F-Filippi.it)  
**Telephone** +39.051.6529611  
**Fax** +39.051.775884