


L	1565 mm
A	235 mm
H	135 mm

ILLUMINOTECHNICAL

Luminous efficiency 100% (DLOR 100%, ULOR 0%).
Initial luminous flux of the luminaire 8903 lm.
Emergency luminaire luminous flux BLF 5.7%.
Symmetric distribution.
Installation Interdistance Transv.D = 1.29 x hu - Long.D = 1.29 x hu.
Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 20.2 - 22.9.
Beam angle: 106° - 113°.
Luminous efficacy 133 lm/W.
Lifetime (L93/B10): 30000 h. (tq+25°C)
Lifetime (L90/B10): 50000 h. (tq+25°C)
Lifetime (L85/B10): 80000 h. (tq+25°C)
Lifetime (L80/B10): 100000 h. (tq+25°C)
Sudden decreased luminous flux after 50000 hours: 0% (C0).
Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471).
In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards.

SOURCE

2 linear LED modules 30W/840.
Energy efficiency class (UE 2019/2020 - UE 2019/2015): C.
CIE 13.3 Colour rendering index: CRI >80 (R9 <50%).
IES TM-30 Fidelity Index: Rf = 84 Rg = 95.
CCT nominal colour temperature 4000 K.
Colour initial tolerance (MacAdam): SDCM 3.

MECHANICAL

Single-piece housing in pressed steel, powder-coated in white epoxy-polyester.
Transparent glass, non-combustible, tempered, mounted and locked to the single-piece galvanised steel perimetrical frame, sealing gasket, hinged opening by means of galvanised steel clips.
Gear-tray unit in hot-galvanised steel, painted in white polyester, fixed to the housing by means of "Ribloc" rapid devices in galvanised steel, hinged opening.
Luminaire with limited surface temperature. - D - (EN 60598-2-24)
Dimensions: 1565x235 mm, height 135 mm.
IP65 protection degree.
Mechanical strength to impacts IK09 (10 joule).
Glow-wire test resistance 960°C.

ELECTRICAL

Halogen Free electronic wiring 230V-50/60Hz, power factor 0.95, THD <25%, constant output current, SELV, class I, 1 driver.
Power of the luminaire 67 W.
CE - IEC 60598-1 - EN 60598-1.
EP maintained emergency wiring on board, 1h duration, 24h recharge; compliant with EN 60598-2-22, excluding high risk areas.
SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light.
Ambient temperature from +5°C to +25°C.
Temperature class T6 max 85°C.
Relative humidity UR: <85%.

INSTALLATION

Ceiling / Suspended / Wall.
All accessories dedicated to this product are available on the Catalog and on our website www.3F-Filippi.com.

APPLICATIONS

In industrial environments, stores and dry, dusty indoor environments, subject to occasional water splashes.

WARNING

Fixture not suitable for cold stores with an ambient temperature <5°C and/or relative humidity >85%.
Luminaire designed for disposal/recycling at end-of-life.
Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Performances are measured and certified by our CTFs2 Photometric Laboratory (EN 13032, IES LM79); Test and Inspections (EN IEC 60598-1, CISPR 15, IEC 61547). Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).